

**ELECTRIC GENERATOR FOR USE WITH A VEHICLE WHEEL**  
**BACKGROUND OF THE INVENTION**

**1. Field of the Invention**

The invention relates to an electric generator, more  
5 particularly to an electric generator for use with a  
vehicle wheel.

**2. Description of the Related Art**

Figure 1 illustrates a conventional electric  
generator 2 for use with a bicycle 1. The conventional  
10 electric generator 2 is mounted on a wheel axle 12 and  
provides electric power to a lamp 13 mounted on the  
bicycle 1.

Referring to Figure 2, the conventional electric  
generator 2 is shown to include a housing 21, three stator  
15 coils 22, and three magnet rings 23. The housing 21  
is secured to a wheel hub 14 on the wheel axle 12 such  
that the housing 21 is capable of rotating about the  
wheel axle 12 when a bicycle wheel 11 (see Figure 1)  
rotates. The stator coils 22, which are connected in  
20 series, are disposed in the housing 21 and are mounted  
on the wheel axle 12. The magnet rings 23 are disposed  
in the housing 21 around the stator coils 22, and are  
mounted on an inner surface of the housing 21.

As such, rotation of the magnet rings 23 with the  
25 housing 21 when the bicycle wheel 11 rotates results  
in an induced electrical current in the stator coils  
22 that is provided to the lamp 12 via a cable 24.

The following are some of the drawbacks of the conventional electric generator 2:

1. The bicycle wheel 11 must be detached when it is desired to install the electric generator 2.

5        2. Variations in speed of rotation of the bicycle wheel 11 results in an unstable induced electrical current such that the service life of the lamp 13 is adversely affected.

#### **SUMMARY OF THE INVENTION**

10        Therefore, the object of the present invention is to provide an electric generator for use with a vehicle wheel that can eliminate the aforesaid drawbacks of the prior art.

      According to the present invention, there is provided  
15        an electric generator adapted for use with a vehicle wheel. The electric generator comprises:

      a housing adapted to be mounted on the vehicle wheel and having a base wall and a surrounding wall that extends from a periphery of the base wall and that cooperates  
20        with the base wall to confine a receiving space, the surrounding wall being formed with inlet and outlet vent holes that are in spatial communication with the receiving space;

      an air impeller disposed in the receiving space and  
25        having a spindle that extends in an axial direction transverse to the base wall and that is coupled rotatably to the base wall, the air impeller being formed with

a plurality of radial impeller blades such that flow of air into the receiving space through the inlet vent hole and out of the receiving space through the outlet vent hole when the vehicle wheel rotates results in  
5 rotation of the air impeller in the receiving space;  
a stator coil mounted securely in the receiving space;  
and

a magnet ring disposed in the receiving space around the stator coil and coupled co-rotatably to the air  
10 impeller such that rotation of the magnet ring with the air impeller results in an induced electrical current in the stator coil.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Other features and advantages of the present  
15 invention will become apparent in the following detailed description of the preferred embodiments with reference to the accompanying drawings, of which:

Figure 1 is a fragmentary schematic view showing a conventional electric generator for use with a bicycle;

20 Figure 2 is a schematic sectional view of the conventional electric generator;

Figure 3 is a perspective view showing the first preferred embodiment of an electric generator for use with a vehicle wheel according to this present invention;

25 Figure 4 is an exploded perspective view showing the first preferred embodiment;

Figure 5 is a schematic sectional view showing the

first preferred embodiment;

Figure 6 is a schematic circuit block diagram illustrating the first preferred embodiment;

Figure 7 is an exploded perspective view showing the  
5 second preferred embodiment of an electric generator for use with a vehicle wheel according to the present invention;

Figure 8 is a fragmentary schematic sectional view showing the second preferred embodiment; and

10 Figure 9 is a fragmentary schematic sectional view showing the third preferred embodiment of an electric generator for use with a vehicle wheel according to the present invention.

#### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

15 Before the present invention is described in greater detail, it should be noted that like elements are denoted by the same reference numerals throughout the disclosure.

Referring to Figures 3 to 6, the first preferred  
20 embodiment of an electric generator 5 for use with a vehicle wheel 4 according to the present invention is shown to include a housing 51, an air impeller 521, a stator coil 522, and a magnet ring 523. In this embodiment, the vehicle wheel 4 includes a metal wheel  
25 body 41 formed with a plurality of fastener holes 42.

The housing 51 is adapted to be mounted on the metal wheel body 41 and to be disposed at a center of the metal

wheel body 41, as shown in Figure 3. The housing 51 has a base wall 511, and a surrounding wall 512 that extends from a periphery of the base wall 511 and that cooperates with the base wall 511 to confine a receiving space 513. The base wall 511 is formed with a spindle sleeve 518 that extends into the receiving space 513. The surrounding wall 512 is formed with inlet and outlet vent holes 516, 517 that are in spatial communication with the receiving space 513. In this embodiment, the housing 51 is formed with opposite mounting lugs 514 that extend radially and outwardly from said surrounding wall 512. Each mounting lug 514 is formed with a lug hole 515 that is aligned with a corresponding one of the fastener holes 42 in the metal wheel body 41 and that permits extension of a corresponding fastener 43 through the lug hole 515 and into the corresponding one of the fastener holes 42 so as to permit fastening of the housing 51 on the vehicle wheel 4. Preferably, the inlet vent hole 516 tapers in a direction toward the receiving space 513.

The air impeller 521 is disposed in the receiving space 513, and has a spindle 525 that extends in an axial direction (A) transverse to the base wall 511 (see Figure 5) and that is coupled rotatably to the base wall 511. In this embodiment, the spindle 525 is mounted rotatably in the spindle sleeve 518. The air impeller 521 is formed with a plurality of radial impeller blades 5211 such

that flow of air into the receiving space 513 through the inlet vent hole 516 and out of the receiving space 513 through the outlet vent hole 517 when the vehicle wheel 4 rotate results in rotation of the air impeller 521 in the receiving space 513.

The stator coil 522 is mounted securely in the receiving space 513. In this embodiment, the stator coil 522 is secured on the spindle sleeve 518, as shown in Figure 5.

The magnet ring 523 is disposed in the receiving space 513 around the stator coil 522, and is coupled co-rotatably to the air impeller 521, as shown in Figure 5, such that rotation of the magnet ring 523 with the air impeller 521 results in an induced electrical current in the stator coil 522.

In this embodiment, the electric generator 5 further includes a circuit board 53, a charging and regulating unit 531, a light emitting module 532, and a light sensor 533, as shown in Figure 6. The circuit board 53 is mounted on the surrounding wall 512 of the housing 51. The charging and regulating unit 531 is mounted on the circuit board 53 and is coupled electrically to the stator coil 522 through a conductor 524. The light emitting module 532 is mounted on the circuit board 53, and is coupled to and is driven by the charging and regulating unit 531. The light sensor 533 is coupled electrically to the charging and regulating unit 531

and the light emitting module 532 for selectively enabling and disabling operation of the light emitting module 532 in accordance with ambient light conditions. For example, the light sensor 533 disables operation of the light emitting module 532 during day time, and enables operation of the light emitting module 532 during night time. Since the charging and regulating unit 531 and the light sensor 533 are known in the art, a detailed description of the same is omitted herein for the sake of brevity.

When the light emitting module 532 rotates with the vehicle wheel 4, a large lighted area is formed as a result of vision persistence so as to achieve a desired warning effect.

It is noted that the induced electrical current generated by the electric generator 5 of the invention can also be applied to an electronic device in a vehicle.

Figures 7 and 8 illustrate the second preferred embodiment of an electric generator 5' for use with a vehicle wheel 4 according to this invention, which is a modification of the first preferred embodiment. Like the previous embodiment, the metal wheel body 41' of the vehicle wheel 4' is formed with a plurality of fastener holes 42'. The electric generator 5' further includes a pair of anchor members 54, each of which is adapted to be disposed in and fastened to the vehicle wheel 4' at a respective one of the fastener holes 42'

by means of a corresponding fastener 43' extending through a through hole 544 that is formed in the anchor member 54. Each of the anchor members 54 has a rim flange 542 adapted to be seated against the metal wheel body 41' of the vehicle wheel 4' outwardly of the respective one of the fastener holes 42'. Each of the mounting lugs 514 is disposed to lie against and is fastened by the corresponding fastener 55 to the rim flange 542 of a respective one of the anchor members 54. It is noted that each of the rim flanges 542 is formed with a plurality of positioning holes 545. The corresponding fastener 55 extends through the lug hole 515 in the mounting lug 514, and engages one of the positioning holes 545 in the anchor member 54 according to the size of the metal wheel body 41'.

Figure 9 illustrates the third preferred embodiment of an electric generator 5" for use with a vehicle wheel according to this invention, which is a modification of the previous embodiments. Unlike the previous embodiments, each anchor member 54' includes an outer positioning tube 546 formed with the ring flange 542, and an inner anchoring seat 547 disposed in the positioning tube 546 and adapted to be fastened to the metal wheel body 41' of the vehicle wheel. In this embodiment, the inner anchoring seat 547 has a sleeve portion positioned in the outer positioning tube 546 by means of a plurality of positioning fasteners 548,

each of which extends through a through hole in the sleeve portion and into a corresponding slot formed in the outer positioning tube 546 such that the inner anchoring seat 547 is movable relative to the outer positioning tube 546 so as to suit vehicle wheels of varying thickness.

The following are some of the advantages attributed to the electric generator 5, 5', 5" of the present invention:

1. Due to the presence of the charging and regulating unit 531, a stable working voltage can be provided to the light emitting module 532 so as not to adversely affect the service life of the light emitting module 532.

2. Due to the presence of the light sensor 533, the induced electrical current accumulated when the light sensor 533 disables operation of the light emitting module 532 can be applied to the light emitting module 532 even when the vehicle wheel is idle.

3. Due to the presence of the anchor members 54, 54', the electric generator 5, 5', 5" of the present invention can be applied to different vehicle wheels.

4. The electric generator 5, 5', 5" of the present invention can be directly installed on the metal wheel body 41, 41' without the need to disassemble the vehicle wheel.

While the present invention has been described in connection with what is considered the most practical

and preferred embodiments, it is understood that this invention is not limited to the disclosed embodiments but is intended to cover various arrangements included within the spirit and scope of the broadest  
5 interpretation so as to encompass all such modifications and equivalent arrangements.